



 EQUINATIVE PRINTING SERIES	CI NO.	Shade 2.0% o.w.f.	Solubility in gpl at 30 °C	Affinity	Reactivity	Fixation Temperature °C at Steaming	Process Suitability				Other Fastness			Light Fastness AATCC 16E			Post Fastness Properties				
							Exhaust	Cold Pad Batch	Printing	Continuous	Washing Fastness ISO 105 C04	Rubbing ISO 105/X12 Dry	Rubbing ISO 105/X12 Wet	0.1%	1.0%	2.0%	Water ISO 105 E01	Chlorinated Pool Water AATCC 162:2002	Hydrogen Peroxide	Perspiration ISO 105 E04 Acid	Perspiration ISO 105 E04 Alkali
Yellow H6G	Yellow 95		80	L	M	110	NS	NS	HS	NS	4	4-5	4	3-4	4	4	4-5	3-4	3-4	4-5	4-5
Yellow H5G	Yellow 2		100	L	M	110	NS	NS	HS	NS	4	4-5	4	3-4	4	4	4-5	3-4	3-4	4	4-5
Yellow H4G	Yellow 18		150	L	M	110	NS	NS	HS	NS	5	4-5	4	4	4	4	4-5	3-4	3-4	4	4-5
Go.Yellow P2RN	Orange 12		100	M	M	110	NS	NS	HS	NS	5	4-5	4	3-4	4	4	4-5	3-4	4-5	4-5	4-5
Orange P2R	Orange 13		100	M	M	110	NS	NS	HS	NS	4-5	4	3-4	3	3-4	4	4-5	3	4	3-4	4
Red PB	Red 24		100	H	L	110	NS	NS	HS	NS	4-5	4	4	3	3-4	4	4-5	3-4	3-4	3-4	4
Red P3B	Red 45		100	M	L	110	NS	NS	HS	NS	4-5	4	3-4	3-4	4	4	4-5	3-4	1	3-4	4
Red P4B	Red 245		150	M	L	110	NS	NS	HS	NS	4-5	4	3-4	3-4	4	4	4	1	1	3-4	4
Red P6B	Red 76		80	M	L	110	NS	NS	HS	NS	3-4	4	3	2-3	3	3-4	3-4	3	3-4	4	4-5
Red P8B	Red 31		80	M	L	110	NS	NS	HS	NS	4-5	3-4	3	2-3	3	3	4-5	3	2-3	3-4	4
Red P8BN	Red*		80	M	L	110	NS	NS	HS	NS	4-5	4	3-4	2-3	3	3	4-5	3-4	2-3	3-4	4
Magenta PB	Violet 13		80	M	L	110	NS	NS	HS	NS	4-5	4	3	3	3	3-4	4-5	2-3	2-3	3-4	4
Turq. Blue H5G	Blue 25		80	H	L	110	NS	NS	HS	NS	2-3	3-4	2-3	3	3	3-4	3	2-3	3	4	4
Blue P3R	Blue 49		100	M	M	110	NS	NS	HS	NS	4-5	3-4	3	3-4	4	4	4	1-2	3	4	4-5
Blue HGR	Blue 5		30	M	L	110	S	S	S	NS	4	4	3-4	3-4	3-4	4	4	1	1	4	4
Blue H5R	Blue 13		80	M	L	110	NS	NS	HS	NS	4	4	3-4	3-4	3-4	4	4	1	1	4	4
Purple P3R	Violet 1		100	M	L	110	NS	NS	HS	NS	4-5	4	3-4	3-4	4	4	5	2-3	2-3	4	4
Navy Blue RX	Blue 79		100	M	M	110	S	S	S	NS	4	4	3-4	--	3	4	4-5	2-3	3	4	4-5
Navy Blue P2R	Black 39		120	L	M	110	NS	NS	HS	NS	4	4	3-4	--	3	3-4	4-5	2-3	3	4	4-5
Red Brown H4R	Brown 9		60	M	L	110	NS	NS	HS	NS	4-5	4	3-4	3	3	3-4	4-5	3	3	4	4
Black HN	Black 8		80	L	M	110	NS	NS	HS	NS	4-5	3-4	3	3	3-4	4	4-5	1	3	4	4
Black PGR	Black*		120	L	M	110	NS	NS	HS	NS	4	4	3-4	--	3	3-4	4-5	2-3	3	4	4-5

H - High | M - Medium | L - Low | HS - High Suitable | S - Suitable | LS - Low Suitable | NS - Not Suitable